



<11 km
Range per Charge



118 kg
Weight Capacity



100.3 cm
Turning Radius



GO GO[®]
ULTRA X

Ultra-Compact for Those on the GO!

Experience worry-free travel with the Go-Go® Ultra X, an ultra-compact scooter designed for effortless disassembly into five lightweight pieces with feather-touch technology. Conveniently access your belongings with the easy-to-reach front basket. This economical scooter ensures mobility and independence without compromising on quality or convenience.





Removable Battery Box




Feather Touch Disassembly



3 or 4 Wheel Option Available

RANGE PER CHARGE (MAX) ¹	Up to 11 km
MAXIMUM WEIGHT CAPACITY	118 kg
TURNING RADIUS	3W: 83.8 cm 4W: 100.3 cm
MAXIMUM SPEED ¹	6.4 km/h
LENGTH & WIDTH ³	3W: L: 94 cm W: 49.5 cm 4W: L: 100.3 cm W: 49.5 cm
SEAT TYPE WIDTH & DEPTH (STANDARD)	Compact, foldable seat W: 43 cm (17") D: 43 cm (17")
SEAT-TO-DECK HEIGHT	40 cm - 43.8 cm
SEAT-TO-GROUND HEIGHT	55 cm - 60 cm
GROUND CLEARANCE ⁵	6.3 cm at midframe 3.8 cm at motor

OVERALL WEIGHT (NOT INC BATTERY) ²	3W: 34.5 kg 4W: 36.3 kg
WEIGHT OF HEAVIEST PIECE	3W: 13.4 kg (front section) 4W: 15.4 kg (front section)
SUSPENSION	N/A
3W/4W OPTION	3W and 4W
FRONT TYRES	3W: 8" solid 4W: 7" solid
REAR TYRES	8" solid
BATTERY REQUIREMENTS ⁴	(2) 12Ah
BATTERY CHARGER	Off-board, 2A
BATTERY WEIGHT	4 kg each
COLOUR OPTIONS	 Red

1. Varies with user weight, terrain type, battery amp hour (Ah), battery charge, battery condition and tyre condition.
2. Includes standard seat weight.
3. Width of base (not including seat).
4. Deep cycle (AGM or gel cell type recommended)
5. Does not account for anti-tip clearance.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3%.