



**<25.2 km**  
Range per Charge



**273 kg**  
Weight Capacity



**67.3 cm**  
Turning Radius



**Jazzy**<sup>®</sup>  
**1450**

## Heavy-Duty Durability

The Jazzy® 1450 is a heavy-duty, bariatric power chair built for exceptional stability and durability. Engineered to support up to 272 kg, it provides a secure and comfortable ride for users needing a higher weight capacity. With a front-wheel drive system and large, knobby tyres, it delivers smooth performance on even or level terrain, ensuring confident maneuverability. Front anti-tip wheels enhance stability, while the rugged frame and efficient motors offer reliable operation for everyday mobility. Designed for strength and comfort, the Jazzy® 1450 is the ideal choice for those seeking a high-capacity power chair for daily use.





Regenerative and Electro-mechanical Braking System



VR2 Joystick Controller



Fold-down Foot Platform

RANGE PER CHARGE (MAX) <sup>1</sup>	Up to 25.2 km
MAXIMUM WEIGHT CAPACITY	273 kg
TURNING RADIUS	67.3 cm
MAXIMUM SPEED <sup>1</sup>	7.2 km/h
LENGTH & WIDTH <sup>2</sup>	L: 97 cm W: 74.2 cm
WEIGHT OF HEAVIEST PIECE	88.4 kg
GROUND CLEARANCE	7.6 cm at foot-board mount 3.8 cm at anti-trip wheel
SEAT SIZE	W: 60.9 cm to D: 81.2 cm (24" to 32")
STANDARD (24") SEAT WEIGHT	25.8 kg
HIGH-BACK SEAT-TO-FLOOR RANGE	52 cm - 57 cm
SPECIALTY SEATING OPTIONS	Synergy® Seating

STANDARD ELECTRONICS	90A, PG VR2
SPECIALTY CONTROLS	Yes
DRIVE TRAIN	Two motor, front-wheel drive
BRAKING SYSTEM	Regenerative and electro-mechanical
SUSPENSION TYPE	Limited
FRONT CASTORS	4" solid anti-tip
DRIVE WHEELS	14" solid
REAR CASTORS	9" solid
BATTERY REQUIREMENTS <sup>3</sup>	(2) 70Ah, 12V
BATTERY CHARGER	8A, off-board
BATTERY WEIGHT	23.4 kg each
COLOUR OPTIONS	Red

- Varies with user weight, terrain type, battery amp hour (Ah), battery charge, battery condition and tyre condition.
- Width of base (not including seat).
- Deep cycle (AGM or gel cell type recommended)

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3%.