



<16.7 km
Range per Charge



136 kg
Weight Capacity



94 cm
Turning Radius



GO GO
ELITE TRAVELLER® 2

Navigate Tight Corners with Ease!

The Go Go Elite Traveller® 2 features the tightest turning radius of all 4-wheel scooters, measuring just 94 cm. With Pride's patented EZ Turn Technology, navigating through tight spaces has never been easier, enabling you to execute U-turns effortlessly on sidewalks, in grocery store aisles, and even in elevators. Additionally, the scooter is equipped with a turning speed sensor that prevents turns at excessive speeds, ensuring safe and controlled manoeuvring. To further personalize your ride, four different coloured interchangeable shrouds are included, allowing you to switch them out whenever you like.





Pride's EZ Turn Technology



All interchangeable shrouds included



Breathable Mesh Seat

RANGE PER CHARGE (MAX) ¹	Up to 16.7 km	OVERALL WEIGHT (NOT INC BATTERY) ²	37.6 kg
MAXIMUM WEIGHT CAPACITY	136 kg	WEIGHT OF HEAVIEST PIECE	15.8 kg (front section)
TURNING RADIUS	94 cm	SUSPENSION	N/A
MAXIMUM SPEED ¹	6.8 km/h	3W/4W OPTION	4W
LENGTH & WIDTH ³	L: 103.6 cm W: 49.4 cm	FRONT TYRES	7" solid
SEAT TYPE WIDTH & DEPTH (STANDARD)	Compact, foldable seat W: 43 cm (17") D: 43 cm (17")	REAR TYRES	8" solid
SEAT-TO-DECK HEIGHT	41.6 cm - 45.3 cm	BATTERY REQUIREMENTS ⁴	(2) 18Ah
SEAT-TO-GROUND HEIGHT	46.3 cm - 51.4 cm	BATTERY CHARGER	Off-board, 2A
GROUND CLEARANCE ⁵	3.4 cm at transaxle	BATTERY WEIGHT	6 kg each
		COLOUR OPTIONS ⁶	■ Red ■ Black ■ Blue White

- Varies with user weight, terrain type, battery amp hour (Ah), battery charge, battery condition and tyre condition.
- Includes standard seat weight.
- Width of base (not including seat).
- Deep cycle (AGM or gel cell type recommended)
- Does not account for anti-tip clearance.
- All shroud panels included

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3%.